



Certificate of Accreditation: Supplement

JASTI Technical Center

669 Yanagisawa Numazu, Shizuoka 410-0308
 Contact Name: Yoshihiro Ozawa Phone: 055-966-8620

Accreditation is granted to the facility to perform the following testing:

FIELD OF TEST	ITEMS, MATERIALS OR PRODUCTS TESTED	SPECIFIC TESTS OR PROPERTIES MEASURED	SPECIFICATION, STANDARD METHOD OR TECHNIQUE USED	RANGE (WHERE APPROPRIATE) AND DETECTION LIMIT
Mechanical ^F	Hybrid-III Test Dummy 50th, 5th Pelvis Ass'y	St-6 Stand Hip Joint Test Stand Hip Joint Test	On the basis of: 49CFR(part572) Subpart E/ SAE J2862 User's Manual for the Small Adult Female H III Test Dummy Measuring instruments: Load Cell Angle Gauge	Angular Velocity: 5.0 °/s to 10.0 °/s Moment: 0 Nm to 203 Nm Angle: 0 ° to 50 ° Temperature: 20.6 °C to 22.2 °C Humidity: 10 % to 70 %
	Hybrid-III Test Dummy 95th, 50th, 5th Knee Ass'y	St-7 Stand Knee Pendulum Test Stand Knee Impact Test Knee Slider Test	On the basis of: 49CFR(part572) Subpart E,O/ SAE J2860 User's Manual for the Hybrid III Large Male Test Dummy/ SAE J2856 User's Manual for the 50th Percentile Male Hybrid III Dummy/ SAE J2876 Low Speed Knee Slider Test Procedure for the H III 50th Male Dummy/ SAE J2862 User's Manual for the Small Adult Female H III Test Dummy Measuring instruments: Accelerometer Load Cell Displacement Gauge	Force: 0 N to 7 300 N Displacement: 0.0 mm to 18.3 mm Velocity: 1.53 m/s to 2.80 m/s Temperature: 18.9 °C to 25.6 °C Humidity: 10 % to 70 %
	Hybrid-III Test Dummy 50th Foot Ass'y	St-8 Stand Foot Pendulum Test Stand Foot Impact Test	On the basis of: ECE Addendum93 : Regulation No.94 Measuring instruments: Accelerometer Load Cell	Acceleration: 0 m/s ² to 3 383 m/s ² Moment: 0 Nm to 145 Nm Force: 0 kN to 3.8 kN Temperature: 19.0 °C to 25.0 °C Humidity: 10 % to 70 %